




INFERNOWARE®



Health	2
Fire	3
Reactivity	0
PPE	G



SECTION 1: CHEMICAL PRODUCT AND COMPANY INFORMATION

Product Name: InfernoWare® Dissipate HDC-1	Supplier Information: 1-734-315-4221
Application: Thermosetting amorphous ceramic compound	InfernoWare LLC
CAS#: <i>Not available</i>	4401 Varsity drive, suite A
RTECS: <i>Not available</i>	Ann Arbor, MI 48108
Document Revision: 1.4	CHEMTREC (24-hour): 1-800-424-9300
Document Revision Date: 2025 December 1st	Poison Control (24-hour): 1-800-222-1222
	For non-emergency assistance: 1-734-315-4221

SECTION 2: HAZARDS IDENTIFICATION

<p>GHS classification in accordance with 29 CFR 1910 (OSHA HCS) Physical, Flammable Liquids, 3 Health, Acute toxicity, 4 Oral, 4 dermal, inhalation 4 Skin Corrosion 2 Serious Eye damage 2A Carcinogenicity 2 Reproductive toxicity 1B Specific target organ toxicity, single exposure 1 (central nervous system, respiratory system, kidney, liver) Specific target organ toxicity, repeated exposure 1 (central nervous system, respiratory system)</p> <p>Signal word Danger</p> <p>Harmful to aquatic life with long lasting effects</p>	GHS hazard statements	
	H226	Flammable liquid or vapors
	H302, 312	Harmful if swallowed or if contact with skin
	H315	Cause skin irritation
	H317	May cause an allergic skin reaction
	H319	Cause serious eye irritation
	H351	Suspected of causing cancer
	H336	May cause drowsiness or dizziness
	H360	May damage fertility or unborn child
	H370	Cause damage to organ, single exposure (central nervous system, respiratory system, kidney, liver)
	H373	May cause damage to organs through prolonged or repeated exposure (central nervous system, respiratory system)
	H412	Harmful to aquatic life with long lasting effects
	GHS precautionary statements	
	P201	Obtain special instructions before use.
P210	Avoid heat/sparks/open flames/hot surfaces.	

	P261	Avoid breathing fumes, mist, and vapor.
	P270	Do not eat, drink or smoke when using this product.
	P271	Use only outdoors or in a well-ventilated area.
	P272	Contaminated work clothing must not be allowed out of the workplace.
	P280	Wear protective gloves/protective clothing/eye protection/face protection.
	P284	Wear respiratory protection.
	P301 P312 P330 P331	IF SWALLOWED: Call a POISON CENTER/doctor. Do not induce vomiting. Rinse mouth.
	P302 P361 P352	IF ON SKIN (or hair): remove immediately all contaminated clothing. Rinse skin with water or shower.
	P304 P340 P312	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
	P305 P338 P351	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.
	P314	Get medical advice/attention if you feel unwell.
	P333 P313	If skin irritation or rash occurs: Get medical advice/attention.
	P363	Wash contaminated clothing before use.
	P370 P378	In case of fire: Use sand or carbon dioxide or powder extinguisher for extinction.
	P403 P235	Store locked up in a well-ventilated place. Keep Cool
	P501	Dispose of contents and containers to an approved facility in accordance with local, regional, national, and international regulations.

SECTION 3: Composition

Name	CAS#	Wt%
Proprietary resin	—	5-50
xylene	1330-20-7	5-60

SECTION 4: FIRST AID MEASURES

General advice	Consult a physician. Provide this data sheet to medical personnel. Move out of dangerous area.
If inhaled	Move person to fresh air. Seek medical attention. If not breathing or unconscious, provide artificial respiration. Exercise caution if performing mouth-to-mouth resuscitation for persons who have inhaled toxic substances.
Skin Contact	Immediately flush skin with large amount of water while removing contaminated clothing and shoes. Wash off with soap and water for at least 15 minutes. If symptoms persist, seek medical attention. Do not peel solidified product off the skin.
Eye Contact	Rinse thoroughly with plenty of water or saline solution for at least 15 minutes, occasionally lifting the upper and lower lid. Remove contact lenses if present and easy to do. Continue rinsing. Consult a physician.
Ingestion	To prevent aspiration of material into the lungs, lay the victim on one side with head lower than the waist. Never give anything by mouth to an unconscious person. Rinse mouth with water, then drink a lot of water. Remove denture if present. Seek medical advice.

SECTION 5: Fire Fighting Measure

Extinguishing media	Suitable methods of extinction: Use only sand, dry chemical or carbon dioxide. Unsuitable methods of extinction: Water jets streams may spread the fire.
Special hazards	Flammable liquid and vapor! Vapors are heavier than air and can travel along the ground to a source of ignition and flash back. Vapors can spread along the ground and collect in low or confined areas. Liquid will float and may reignite on the surface of water.
Advice for firefighters	Wear self-contained breathing apparatus for firefighting if necessary.
Further information	Use water spray to cool unopened containers.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	Avoid breathing mist or vapors. Wear respiratory protection. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapor accumulation in low-lying areas.
Environmental precautions	Prevent further leakage or spillage, if practical and safe. Do not allow product to enter drains. Avoid discharge into the environment.

Methods and materials for containment and remediation	Stop leak if possible and safe. Cover spill with vermiculite, perlite or ground clay. Do not use combustible material such as saw dust. Sweep up and store in appropriate waste container for disposal via a licensed waste disposal company.
--	---

SECTION 7: HANDLING AND STORAGE

Precautions for safe handling:	<p>This material is flammable: Avoid vapor formations and use with adequate ventilation, avoid breathing fumes. Vapors are heavier than air and will tend to collect in low areas. Avoid use in confined spaces. Flammable vapors may form explosive mixtures in the air. Ground coating equipment and containers at all times. Use non sparking tools. Isolate, vent, drain, wash and purge systems or equipment before maintenance or repair.</p> <p>Avoid bodily contact with material: Wear appropriate personal protective equipment. Avoid contact with skin and eyes. Wash hands thoroughly after handling and avoid contact with eyes. No eating, drinking or smoking near areas where substance is handled, processed or stored.</p>
Conditions for safe storage, including incompatibilities	Keep container clearly labeled and tightly closed in a cool, dry, well-ventilated area. Opened containers must be carefully resealed and kept upright to prevent leakage. Keep away from heat, flames, static electricity. Containers are hazardous when empty as they contain product residues. Ventilate closed areas. Keep out of reach of children.

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Control: Adequate room ventilation plus local exhaust at points of emission to maintain levels of airborne contaminants below exposure limits. Assure ACGIH TWA and OSHA PEL limits (varies by product) are maintained. Use of fume hoods or closed booths required when product is used in a manner that may generate mist or aerosol.

Personal Protective Equipment:

Hands: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times. Solvent resistant (neoprene, nitrile or other nonporous) recommended.

Eyes: Chemical splash goggles should be worn at a minimum.

Skin: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Apron and protective industrial coating recommended.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Dark liquid	Evap. Rate:	0.6
Physical state:	Liquid	Decomp Temp:	Not Available
Density:	0.8 - 1.4 g/cm ³	Odor:	Organic solvent
Viscosity:	50-100 Cp	Solubility:	negligible
Boiling Point:	>136 °C	Freezing/Melting pt.:	Not Available

Flammability:	Flammable	Flash Point:	25 °C, closed cup
Partition Coefficient	Not Available	Vapor Density:	Not Available
Vapor Pressure	Not Available	VOC:	>60wt%
pH:	N/A	Auto-ignition Temp:	464 °C
		UFL/LFL:	1v/v%-6.8v/v%

SECTION 10: STABILITY AND REACTIVITY

Hazardous polymerization	No
Hazardous Decomposition	Thermal decomposition products include oxides of carbon.
Materials to avoid	Strong oxidizers
Chemical stability	Stable

SECTION 11: TOXICOLOGICAL INFORMATION

NTP Carcinogen: No IARC Monographs: 2B OSHA Regulated: Yes (435mg/m3)
Xylene is classed 2B by the International Agency for Cancer Research (IARC).
 Reported Human Effects: No human studies have been conducted with this material. The use of recommended protective equipment should minimize any adverse effects.

Based on sums of components, following animal effects are expected:
 Oral LD50, rat: 1000 mg/kg

SECTION 12: ECOLOGICAL INFORMATION

Harmful to aquatic life with long lasting effects.
 Xylene
Acute and prolonged toxicity to fish : LC50 rainbow trout 96h 2.6mg/l
Toxicity to aquatic invertebrates EC50 Daphnia magna (water fleas)9d 0.96mg/L

Avoid disposal in Landfills and sewage systems. Avoid releases into water sources

SECTION 13: DISPOSAL CONSIDERATIONS

This product, as well as any materials impregnated or infused with it during its use, must be disposed of in accordance with all applicable local, state and federal regulations. Contact a licensed professional waste disposal service to dispose of this material

SECTION 14: TRANSPORT INFORMATION

UN 3469 (Paint, flammable, corrosive)

US DOT and IATA

Proper Shipping Paint, flammable, corrosive

Hazard Class: 3[8]

UN Number 3469

Packing Group: III

SECTION 15: REGULATORY INFORMATION

Component	CAS#	Wt%	Regulations
Proprietary resin	—	5-50	TSCA, PA, M, NJ
xylene	1330-20-7	5-60	TSCA, MA, PA, CA prop. 65

PA = PA Right-To-Know List of Hazardous Substances

M=Massachusetts Right-To-Know List of Hazardous Substances

NJ= New Jersey Right-To-Know List of Hazardous Substances

DE= Delaware Right-To-Know List of Hazardous Substances

NY= New York Right-To-Know List of Hazardous Substances

PA= Pennsylvania Right-To-Know List of Hazardous Substances

RI= Rhode Island Right-To-Know List of Hazardous Substances

WI= Wisconsin Right-To-Know List of Hazardous Substances

CA Prop. 65 = Safe Drinking Water and Toxic Enforcement Act

TSCA = Toxic Substances Control Act

The following are on California Prop65 list:

Xylene

InfernoWare coatings meet all air quality and regulatory requirements with respect to manufacturing and application. Specifically, the hardened finished product does not release any "volatile organic compounds" (VOC) under any ambient conditions.

U.S. TOXIC SUBSTANCES CONTROL ACT: All components of this product are on the TSCA Inventory or are exempt from the TSCA Inventory requirements under 40 CFR 720.30.

SECTION 16: OTHER INFORMATION**NFPA**

Health=2

Fire=3

Reactivity=0

Specific Hazard=No

HMIS

Health=2

Fire=3

Physical Hazard=0

PPE: G- Safety Glasses, Gloves, Vapor respirators

OSHA Standard 29 CFR 1910.1200 requires that information be provided to employees regarding the hazards of chemicals by means of hazard communication program including labeling, material safety data sheets, training and access to written records. We request that you (as it is your legal duty to) make all information in this Safety Data Sheet available to all your employees.

This document and its contents are copyright 2022 InfernoWare LLC. License granted to make unlimited copies for internal use, subject to the terms of all applicable confidentiality and non-disclosure agreements. Information contained in this literature is offered for use by technically qualified personnel at their own discretion and risk. All statements and information contained herein are provided in good faith. While based on analytic procedures believed to be reliable, InfernoWare makes no express or implicit guarantee regarding their accuracy or completeness. As InfernoWare exercises no control over the end use of the product described herein, it assumes no liability for loss or damage incurred therefrom.